

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier **INTERACRYL PLAST**

1.2. Relevant identified uses of the substance or mixture and uses advised against
 Product is used for manufacturing of custom trays in dental laboratory.

1.3 Details of the supplier of the safety data sheet

	<i>Production:</i>	
Manufacturer/Supplier:	INTERDENT d.o.o.	INTERDENT d.o.o.
Street:	Opekarniška cesta 26	Dol 1
Country code /Postal code/City:	SI-3000 Celje	SI-3342 Gornji Grad
Telephone:	+386(0) 425-62-00	
Fax:	+368(0) 490-62-02	

1.4 Emergency telephone number

Emergency phone: 112 (EU)
+386(0) 425-62-00 (Mon. – Fri.: 8.00 – 16.00)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008.

Hazardous class	Hazard category	Hazard statement
Flammable liquids	2	H225 Highly flammable liquid and vapour.
Specific target organ toxicity – Single exposure	3	H335 May cause respiratory irritation.
Skin corrosion/irritation	2	H315 Causes skin irritation.
Sensitisation – Skin	1	H317 May cause an allergic skin reaction
Serious eye damage/eye irritation	2A	H319 Causes serious eye irritation

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008:

Safety Data Sheet

Hazard pictograms:**Signal word: DANGER****Hazard statements:**

H225 Highly flammable liquid and vapour.
H335 May cause respiratory irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation

Precautionary statements:*Prevention*

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of soap and water

Disposal

P501 Dispose of contents/container in accordance with local regulations.

Contains:

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate, ethyl methacrylate

2.3 Other hazards

PBT and vPvB evaluations are in section 12.5

Safety Data Sheet

SECTION 3: Composition / information on ingredients

3.1 Substance

See section 3.2

3.2 Mixture

UV adsorber CAS 2440-22-4 <<1

Chemical name	CAS Nr. INDEX number EC-Number REACH-no	%	Classification according EC 1272/2008	
			Hazardous class/hazardous category	Hazardous phrases
Methyl-methacrylat; methyl 2-methylprop-2-enoate; methyl 2-methylprope noate	80-62-6 201-297-1 607-035-00-6 01-2119452498- 28	> 80	Flamm.Liq.2 STOT SE 3 Skin Irrit.2 Skin Sens. 1	H225 H335 H315 H317
Ethyl methacrylate	97-63-2 202-597-5 607-071-00-2 01-2119490215- 40	< 20	Flam. Liq. 2 Skin Irrit. 2 Skin Sens. 1 Eye Irrit. 2 STOT SE 3	H225 H319 H335 H315 H317
N,N-dimethyl-p-toluidine	99-97-8 202-805-4 612-056-00-9 01-2119937766- 23	< 1	Acute Tox.3 Acute Tox.3 Acute Tox.3 STOT RE 2 Aquatic Chr 3	H331 H311 H301 H373 H412

Safety Data Sheet

SECTION 4: First Aid Measures

4.1 Description of first aid measures

Inhalation:

Immediately remove victim to fresh air. Keep victim at rest in half upright position. If breathing is difficult: mouth-to mouth resuscitation. If not breathing: artificial aspiration. Immediately get medical attention.

Skin contact:

Wash off with plenty of water for at least 15 minutes. Remove contaminated clothing. (Do not pull loose.) Wash off with plenty of water. Immediately get medical attention.

Eye contact:

Immediately wash out with plenty of water with the eyelid held wide open for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. Immediately get medical attention.

Ingestion:

Safety Data Sheet

Never give anything by mouth to an unconscious person. Do not induce vomiting. Wash out mouth with water. Make victim drink water. Keep victim at rest. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation: Irritating to respiratory system. Exposure may result in depressed respiration, coughing, nausea and sore throat. Prolonged or repeated exposure to large amounts may cause damage to lungs (lung edem).

Ingestion: Irritating to mouth, throat and oesophagus. Exposure may result in sore throat, nausea, retching and blisters. Prolonged or repeated exposure to large amounts may result in unconsciousness or coma.

Skin contact: Irritating to skin. Exposure may result in redness, swelling and pain. Prolonged or repeated skin contact (sweating, fever, pain) In oversensitive people even exposure to very small amounts causes allergic reactions.

Eye contact: Irritating to eyes. Exposure may result in impaired vision, tears, redness and pain.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment: First aid, decontamination, treatment of symptoms.

Notes for the doctor: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable:

Dry chemical, AFFF, foam, carbon dioxide. In extreme cases, if aforementioned extinguishing agents are ineffective in fighting a large fire, use a halon extinguisher.

Unsuitable:

Do not extinguish with water.

5.2 Special hazards arising from the substance or mixture

Vapour is heavier than air and travels along the ground with the risk of distant ignition. Burning may produce: carbon dioxide, carbon monoxide. Fight fires from a protected location. Dyke fire control water for later disposal. Cool exposed containers with water spray.

5.3 Advice for firefighters

Safety Data Sheet

Burning may produce: toxic and /or corrosive vapours/gasses. Use breathing apparatus (self – contained breathing apparatus with full face shield.) Wear suitable protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

In the event major spillage. Evacuate room. Contact safety officer immediately. Wear suitable protective clothing, gloves and eye/face protection.

6.2 Environmental precautions

Prevent dispersion. Do not allow enter sewage system. In the event of major spillage. Contact safety officer immediately.

6.3 Methods and material for containment and cleaning up

Incentive /Danger of explosion. Keep away from sources of ignition. Seal leak if possible without risk. Prevent dispersion. Clean up only under supervision of an expert. Collect spilled material in sealable containers. Absorb remainder in sand or other inert material. Collect in sealable containers.

6.4 Reference to other sections

Safe handling: see section 7. Personal protection equipment: see section 8. Disposal: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

When handling the product, allow for materials and conditions which should be avoided (see Chapter 10). Avoid exposure. Use appropriate protection (see section 8). Take precautionary measures against static discharges. Keep away from open flame, sparks or sources of ignition. Explosion protected electrical equipment.

7.2 Conditions for safe storage, including any incompatibilities

Store in fireproof location. When storing the product, allow for materials and conditions which should be avoided (see section 10). Ventilation required along the floor. Keep container tightly closed. Keep in labeled containers.

7.3. Specific end use(s)

Product is used for repairing of dental prosthesis in dental laboratory.

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum permissible concentrations in the working environment:

Methyl methacrylate (EU - Commission Directive 2009/161 / EU, Official Gazette of the RS No. 78 / 4.12.2018): MV (8 h) = 210 mg / m³ (50 ppm)

8.2 Exposure controls

Engineering measures:

In the event of use above flash point. Use in closed systems. Do not use compressed air by filling, discharging or handling the product. Ventilation required along the floor. ventilation required. Explosion protected electrical equipment. Explosion proof lighting. Earth connection against static electricity. Spark – free tool. Do not heat.

Hygiene measures:

Follow good hygiene practice. Keep personal protective equipment separate from other clothing. Contaminated clothing should be removed immediately. Do not eat, drink or smoke during use. Wash hands after each use.

Personal protective equipment:

With adequate ventilation, extraction or in closed systems breathing apparatus is not required. Chemical hazard measurements. In case of increased exposure and insufficient ventilation, use respiratory protection:

Respiratory system: SIST EN 140: 1999 / AC: 2000 with filter SIST EN 14387: 2004 + A1: 2008 protection filter type A.

Skin and body:

Mandatory use of gloves SIST EN 374: 2004. Butyl gloves (0.7 mm), permeation time 60 min. In practice, depending on the different exposure conditions, this information is used to assist in the selection of appropriate protective gloves. Information is not a substitute for end-user tests. It is necessary to choose the appropriate type of gloves according to the working conditions. There are several types of protective gloves available. Gloves made of elastomeric materials include latex (natural rubber), neoprene (polyisoprene), nitrile gloves (ABS rubber), butyl gloves, polyvinyl alcohol (PVA), polyvinyl chloride (PVC) and fluoroelastomers. Multilayer gloves are made of layers of PVA sandwiched between layers of polyethylene. In the permeability test, PVA / polyethylene multilayer and PVA supported gloves showed the best results (PVA becomes ineffective on contact with water if other layers are damaged). Butyl and nitrile gloves offer only short-term protection. Surgical gloves offer insufficient effective protection. Gloves should be stored and changed regularly, especially with prolonged use of the chemical.

Safety Data Sheet

Eye protection: Mandatory use of safety goggles SIST EN 166: 2002.

Other: When handling large quantities: face mask, chemical-resistant boots, rubber apron.

8.3 Environmental exposure controls

General instructions: Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	Colourless
Odour	Ester-like
Boiling point	100,5 °C
Melting point	- 48 °C
Vapour pressure	3.600 Pa (20°C)
Density	0.94 g/ml at 20°C
Solubility in water	miscible with most organic solvents. Water: 1.6 % slightly soluble
pH	n.a.
Flash point	10°C
Auto ignition temperature	421 °C

Safety Data Sheet

Lower explosion limit	2.1 volume %
Upper explosion limit	12.5 volume %
Viscosity	0.6 mPa.s

9.2 Other information

No additional information relevant to safe use.

SECTION 10: Stability and reactivity

10.1 Reactivity

Not reactive under normal conditions and proper use.

10.2 Chemical stability

Stable under normal conditions. When incorrectly used: Fire hazard, polymerization (stable with: hydrochinon).

10.3 Possibility of hazardous reaction

Data not available.

10.4 Conditions to avoid

Keep away from: open flame and sources of ignition. Do not heat. Protect from (sun)light and heat.

10.5 Incompatible materials

Keep away from: oxidizing substances.

10.6 Hazardous decomposition products

Not known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity

(dermal) : Not classified Acute toxicity

(inhalation) : Not classified

Mutagenicity: Ames – Test: Not mutagenic.

Chemical name: methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

Acute toxicity- Oral: LD₅₀ (rat): 7900 – 9400 mg/kg

Acute toxicity - Dermal: LD₀ (rabbit): >5000 mg /kg

Acute toxicity - Inhalation: LD₅₀ (rat, 4 hour): cca. 29,8 ml / l

Vapour of methyl methacrylate can tease respiratory organs, eyes and skin. Skin exposure can lead to dermatitis. Inhalation can cause dizziness, nausea and vomiting. Long term exposure can cause asthma.

Safety Data Sheet

Skin irritation (rabbit): slightly irritating
Eye irritation (rabbit): slightly irritating
Sensitization (guinea pig): not sensitizing

Chemical name: Ethyl methacrylate (97-63-2)

LD50 oral rat 13424 mg/kg

LC50 Inhalation - Rat 55 mg/l/4h

Chemical name: N, N-dimethyl-p-toluidin

LD50 oral rat 1650 mg/kg

LD50 oral 139 mg/kg bodyweight Animal: mouse,

Guideline: other: LD50 dermal rabbit 2000 mg/kg

LC50 Inhalation - Rat 1.4 mg/l/4h

Skin sensitivity: light irritant

Eye sensitivity: light irritant

Safety Data Sheet

SECTION 12: Ecological information

12.1 Toxicity

No ecological information is known about the product but some is available on the ingredients defined in section 2.

Chemical name: Methyl-methacrylate

Ecologically toxic:

LC 50 (Iepomis macrochirus, 96 hour): 191 mg /l

EC 50 (Daphnia magna, 48 hour): 69 mg /l

Stability in water: Hydrolysis is not significant at neutral or acid pH.

Adsorption in soil-air: MMA volatiles rapidly from soil.

PNECaqua=740µg/l

PNECmicroorganisms = 100 mg/l

PNECsoil_porewater=740µg/l

Chemical name: N, N dimethyl-p-toludin

Ecologically toxic: LD 50 (fish, 96 hour): 46 mg /l

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

Safety Data Sheet

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effect

No data available

SECTION 13: Disposal considerations
13.1 Waste treatment methods

Methods of disposal: Disposal according to the local legislation.

Waste of residues: Keep waste separate. Because of possible pollution, remove as industrial waste or hazardous waste.

Contaminated packaging: Keep waste packaging separate. Because of possible pollution, remove as industrial waste or hazardous waste.

Category of disposal: 16 03 05* Organic wastes containing dangerous substances.

SECTION 14: Transport Information

	Land-Road/Railway (ADR/RID):	Inland waterways (ADNR):	Sea (IMDG):	Air (IATA):
14.1 UN number	UN 1247	UN 1247	UN 1247	UN 1247
14.2 UN proper shipping name	methyl methacrylate, stabilized	methyl methacrylate, stabilized	methyl methacrylate, stabilized	methyl methacrylate, stabilized
14.3 Transport hazard class(es)				
Class	3	3	3	3
Hazard identification number	339	/	/	/
Classification group	F1	/	/	/
Hazardous label	3	/	/	/
Tunnel restriction code	(D/E)	/	/	/
Medical First	/	/	330	

Safety Data Sheet

Aid Guide:				
EmS	/	/	F-E, S-D	/
14.4 Packing group	II	/	II	II
14.5 Environmental hazards	No data available			
14.6 Special precautions for user	No special precautions			
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	No data available			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Product is classified in accordance with directive EC 1907/2006 and 1272/2008 and additional changes or national legislation Ur.l. RS 101/2002 and Ur.l.RS 16/2008.

15.2 Chemical safety assessment

No data available.

SECTION 16: Other information

Revision:

Version 07 issued on May 2023 in accordance with EC 1907/2006 (Commission Regulation (EU) 2015/830) and EC 1272/2008.

Revision in accordance to changes in COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Legend of abbreviations:

ADR - Accord européen relatif au transport international des marchandises dangereuses par route

CAS - Chemical Abstracts Service

CLP – Classification, labeling and packigiong

CMR - Carcinogenic, Mutagenic or toxic for Reproduction

DNEL - Derived No-Effect Level

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

In accordance with Regulation (EC) No. 1907/2006 and (EC) No. 1272/2008

Safety Data Sheet

GHS "Globally Harmonized System of Classification and Labelling of Chemicals"

IATA International Air Transport Association

IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA)

ICAO International Civil Aviation Organization

IMDG International Maritime Dangerous Goods Code

PBT persistent bioaccumulative, toxic

PNEC Predicted No-Effect Concentration

ppm parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Règlement concernant le transport International ferroviaire des marchandises Dangereuses št.

vPvB very Persistent and very Bioaccumulative (zelo obstojno in se zelo lahko kopiči v organizmih)

References:

Safety data sheets of the producer of the raw material for the product

Official gazette RS 36/99, 45/00, 104/00, 101/02, 9/03, 65/03; Official gazette RS št. 78 / 4.12.2018, 78/19; 72/21

European convention about international transport of hazardous material ADR

EC directive 1907/2006 and 1272/2008

Disclaimer of expressed and implied warranties:

The information contained in the safety data sheet is correct to the best of our knowledge at the date of issue. It is intended as a guide for the safe use, handling, disposal, storage and transportation and is not intended as warranty or as a specification. The information relates only to the product specified and may not be suitable for combinations with other materials or in processes other than those specifically described herein.